Please amend the claims as follows:

1. (Currently Amended) ~~Method~~ A method for encoding a stream of input words into a stream of code words using a channel code for storage of the stream of code words on a recording medium comprising tracks for storage of the stream code words, said method comprising the ~~steps~~ step of:

[[-]] coding the stream of input words into the stream of code words,

characterized in that the method further comprises the ~~following~~ steps of:

[[-]] determining a control point in the data stream of input words or the stream of code words where the data stream of input words or the stream of code words can be altered by an alteration~~,~~;

[[-]] for each alteration of a group of N possible alterations, determining, between a group of code words in a first track and a group of code words in a second track which is adjacent to a third track which is adjacent to the first track, a crosstalk value representing the cross talk affecting the third track corresponding to the alteration~~,~~;

[[-]] ~~Selecting~~ selecting an optimum alteration, where the optimum alteration is that alteration from the group of N alterations which has a lowest cross talk value~~,~~; and

[[-]] ~~Altering~~ altering the data stream using the optimum alteration.

2. (Currently Amended) ~~Method~~ The method for encoding a stream of input words into a stream of code words using a channel code as claimed in claim 1, characterized in that N = 2.

3. (Currently Amended) ~~Method~~ The method for encoding a stream of input words into a stream of code words using a channel code as claimed in claim 2, characterized in that the control point is a bit insertion point.

4. (Currently Amended) ~~Method~~ The method for encoding a stream of input words into a stream of code words using a channel code as claimed in claim 1, characterized in that the control point is a code word replacement point.

5. (Currently Amended) ~~Method~~ The method for encoding a stream of input words into a stream of code words using a channel code as claimed in claim 1, characterized in that the control point is determined in the stream of input words.

6. (Currently Amended) ~~Method~~ The method for encoding a stream of input words into a stream of code words using a channel code as claimed in claim 1, characterized in that control point is determined in the stream of code words.

7. (Currently Amended)   ~~Method~~ The method for encoding a stream
of input words into a stream of code words using a channel code as
claimed in claim 1, characterized in that a crosstalk value is
determined calculating a digital sum value of an exclusive NOR
operation performed bitwise on the group of code words in the first
track and the group of code words in the second track.

8. (Currently Amended)   ~~Method~~ The method for encoding a stream
of input words into a stream of code words using a channel code as
claimed in claim 1, characterized in that the group of code words
in the first track is limited to a section of the first track and
that the group of code words in the second track is limited to a
section of the second track and that the section of the first track
is aligned perpendicular to a reading direction of the first track
with the section of the second track.

9. (Currently Amended)   ~~Method~~ The method for encoding a stream
of input words into a stream of code words using a channel code as
claimed in claim 8, characterized in that the bitwise exclusive NOR
function includes a weighing function reflecting a physical
distance.

10. (Currently Amended)   ~~Encoder~~ An encoder for encoding a
stream of input words into a stream of code words using a channel
code for a recording medium comprising tracks for storage of the

stream of code words, said encoder comprising coding means for
encoding the stream of input words into a stream of code words,
characterized in that the encoder further comprises:

[[-]] ~~Control~~ control point alteration means ~~with~~ having an
input for receiving a data stream and an output connected to the
encoding means where the control point alteration means is
operative to determine a control point in the data stream at the
input where the data stream can be altered, and to alter the
control point in accordance with an alteration instruction received
on a alteration instruction input~~.~~;

[[-]] crosstalk determination means ~~with~~ having an input
connected to ~~the~~ an output of the encoding means and an output,
said crosstalk determination means being operative to determine a
first crosstalk value for a first control point alteration and a
second crosstalk value for a second control point alteration~~.~~; and

[[-]] ~~Selection~~ selection means ~~operative with~~ having an input
connected to the output of the crosstalk determination means and an
output connected to the alteration instruction input of the control
point alteration means, said selection means being operative to
select a control point alteration corresponding to the lowest
crosstalk value of the first crosstalk value and the second
crosstalk value.

11. (Currently Amended) ~~Encoder according to~~ The encoder as
claimed in claim 10, characterized in that the crosstalk
determination means is operative to process a group of code words

in a first track of the recording medium and a group of code words in a second track of the recording medium which is adjacent to a third track of the recording medium which is adjacent to the first track of the recording medium, when determining a crosstalk value representing the cross talk affecting the third track.

12. (Currently Amended) ~~Recording~~ A recording device comprising the encoder as claimed in claim 10.

13. (Currently Amended) ~~Recording~~ A recording medium comprising tracks comprising a stream of code words, characterized in that the stream of code words comprises a first data block in a first track and a control point, corresponding to the first data block, added to the stream of code words and inserted in the track, the control point having a value, where the value is based on a cross talk between the first data block in ~~a~~ the first track and a second data block in a second track, where the second track is adjacent to a third track which is adjacent to the first track.